

HANCOR HEAVY DUTY PIPE SPECIFICATION

Scope

This specification describes 3- through 8-inch (75 to 200 mm) Hancor Heavy Duty pipe for use in gravity-flow drainage applications.

Pipe Requirements

Hancor Heavy Duty pipe shall have annular interior and exterior corrugations.

- 3- through 6-inch (75 to150 mm) shall meet ASTM F405;
- 8-inch (200mm) shall meet ASTM F667.

Joint Performance

Joints for 3- to 8- inch (75 – 200 mm) shall be made with split or snap couplings. Standard connections shall meet the requirements of the ASTM F405 or ASTM F667. Gasketed connections shall incorporate a closed-cell synthetic expanded rubber gasket meeting the requirements of ASTM D1056 Grade 2A2. Gaskets, when applicable, shall be installed by the pipe manufacturer.

Fittings

Fittings shall conform to ASTM F405 or ASTM F667.

Material Properties

Pipe and fitting material shall be high density polyethylene conforming with the minimum requirements of cell classification 423410C as defined and described in the latest version of ASTM D3350; or ASTM D1248 Type III, Class C, Category 4, Grade P33.

Installation

Installation shall be in accordance with ASTM D2321 and Hancor installation guidelines, with the exception that minimum cover in trafficked areas for 4- through 8-inch (100 to 200 mm) diameters shall be one foot (0.3 m). Contact your local Hancor representative or visit our website at www.hancor.com for a copy of the installation guidelines.

Pipe Dimensions

Nominal Diameter, in. (mm)					
Pipe I.D. In (mm)	3 (75)	4 (100)	5 (125)	6 (150)	8 (200)
Pipe O.D.* in (mm)	3.6 (91)	4.6 (117)	5.6 (142)	7.0 (178)	9.5 (241)
Perforations	All diameters available with or without perforations.				

*Pipe O.D. values are provided for reference purposes only, values stated for 3- through 8-inch are ± 0.5 inch. Contact a sales representative for exact values.

